



IES ROAD REPORT

PHOTOMETRIC FILENAME : GCL2-80J-MV-27K-3F-XX-260 S.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
 [TESTLAB] Scaled from NVLAP LM-79 for GCL2-80J-MV-30K-3F-XX-275
 [ISSUEDATE] 6/24/2019
 [MANUFAC] Leotek Electronics USA LLC
 [LUMCAT] GCL2-80J-MV-27K-3F-XX-275


CHARACTERISTICS

IES Classification	Type III
Longitudinal Classification	Medium
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	27377
Downward Total Efficiency	N.A. (absolute)
Total Luminaire Efficiency	N.A. (absolute)
Luminaire Efficacy Rating (LER)	133
Total Luminaire Watts	206
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	17792.4
Maximum Candela Angle	60H 73V
Maximum Candela (<90 Degrees Vertical)	17792.4
Maximum Candela At 90 Degrees Vertical)	60H 73V
Maximum Candela At 90 Degrees Vertical	0 (0.0% Luminaire Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	2437.3 (8.9% Luminaire Lumens)
Cutoff Classification (deprecated)	N.A. (absolute)

LUMINAIRE CLASSIFICATION SYSTEM (LCS)

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	2275.7	N.A.	8.3
FM - Front-Medium (30-60)	9129.6	N.A.	33.3
FH - Front-High (60-80)	8160.1	N.A.	29.8
FVH - Front-Very High (80-90)	137.4	N.A.	0.5
BL - Back-Low (0-30)	2060.7	N.A.	7.5
BM - Back-Medium (30-60)	3935.0	N.A.	14.4
BH - Back-High (60-80)	1650.7	N.A.	6.0
BVH - Back-Very High (80-90)	27.9	N.A.	0.1
UL - Uplight-Low (90-100)	0.0	N.A.	0.0
UH - Uplight-High (100-180)	0.0	N.A.	0.0
Total	27377.1	N.A.	100.0
BUG Rating	B3-U0-G4		


COEFFICIENTS OF UTILIZATION



FLUX DISTRIBUTION


	Lumens	Percent Of Luminaire
Downward Street Side	19702.9	72.0
Downward House Side	7674.2	28.0
Downward Total	27377.1	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	27377.1	100.0

POLAR GRAPH




Maximum Candela = 17792.4 Located At Horizontal Angle = 60, Vertical Angle = 73
1 - Vertical Plane Through Horizontal Angles (60 - 240) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (73) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



Distance In Units Of Mounting Height
 Values Based On 20 Foot Mounting Height
 1/2 Maximum Candela Trace Shown As Dashed Curve
 (+) = Maximum Candela Point

LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:
Front: Low=2275.7, Medium=9129.6, High=8160.1, Very High=137.4
Back: Low=2060.7, Medium= 3935.0, High=1650.7, Very High=27.9
Uplight: Low=0.0, High=0.0

BUG Rating : B3-U0-G4