



IES ROAD REPORT

PHOTOMETRIC FILENAME : GCL1-80J-MV-27K-2R-XX-190 S.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TESTLAB] Scaled from NVLAP LM-79 for GCL1-80J-MV-30K-2R-XX-240
[ISSUE DATE] 6/20/2019
[MANUFAC] Leotek Electronics USA LLC
[LUMCAT] GCL1-80J-MV-27K-2R-XX-190


CHARACTERISTICS

IES Classification	Type II
Longitudinal Classification	Medium
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	18588
Downward Total Efficiency	N.A. (absolute)
Total Luminaire Efficiency	N.A. (absolute)
Luminaire Efficacy Rating (LER)	141
Total Luminaire Watts	132
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	11660.419
Maximum Candela Angle	75H 72.5V
Maximum Candela (<90 Degrees Vertical)	11660.419
Maximum Candela At 90 Degrees Vertical	75H 72.5V
Maximum Candela At 90 Degrees Vertical	0 (0.0% Luminaire Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	3014.562 (16.2% Luminaire Lumens)
Cutoff Classification (deprecated)	N.A. (absolute)

LUMINAIRE CLASSIFICATION SYSTEM (LCS)

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	2038.7	N.A.	11.0
FM - Front-Medium (30-60)	7395.6	N.A.	39.8
FH - Front-High (60-80)	4208.6	N.A.	22.6
FVH - Front-Very High (80-90)	125.8	N.A.	0.7
BL - Back-Low (0-30)	1341.4	N.A.	7.2
BM - Back-Medium (30-60)	2205.6	N.A.	11.9
BH - Back-High (60-80)	1224.1	N.A.	6.6
BVH - Back-Very High (80-90)	48.4	N.A.	0.3
UL - Uplight-Low (90-100)	0.0	N.A.	0.0
UH - Uplight-High (100-180)	0.0	N.A.	0.0
Total	18588.2	N.A.	100.0
BUG Rating	B3-U0-G3		


COEFFICIENTS OF UTILIZATION



FLUX DISTRIBUTION

	Lumens	Percent Of Luminaire
Downward Street Side	13768.7	74.1
Downward House Side	4819.5	25.9
Downward Total	18588.2	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	18588.2	100.0

POLAR GRAPH




Maximum Candela = 11660.419 Located At Horizontal Angle = 75, Vertical Angle = 72.5

1 - Vertical Plane Through Horizontal Angles (75 - 255) (Through Max. Cd.)


2 - Horizontal Cone Through Vertical Angle (72.5) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



Distance In Units Of Mounting Height
 Values Based On 20 Foot Mounting Height
 1/2 Maximum Candela Trace Shown As Dashed Curve
 (+) = Maximum Candela Point

LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:
Front: Low=2038.7, Medium=7395.6, High=4208.6, Very High=125.8
Back: Low=1341.4, Medium=2205.6, High=1224.1, Very High=48.4
Uplight: Low=0.0, High=0.0

BUG Rating : B3-U0-G3