



IES ROAD REPORT

PHOTOMETRIC FILENAME : GCL2-80J-MV-27K-4-XX-230 S.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TESTLAB] Scaled from NVLAP LM-79 for GCL2-80J-MV-30K-4-XX-225

[ISSUEDATE] 6/20/2019

[MANUFAC] Leotek Electronics USA LLC

[LUMCAT] GCL2-80J-MV-27K-4-XX-240


CHARACTERISTICS

IES Classification	Type IV
Longitudinal Classification	Medium
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	23027
Downward Total Efficiency	N.A. (absolute)
Total Luminaire Efficiency	N.A. (absolute)
Luminaire Efficacy Rating (LER)	133
Total Luminaire Watts	173
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	13293.394
Maximum Candela Angle	80H 71.5V
Maximum Candela (<90 Degrees Vertical)	13293.394
Maximum Candela Angle (<90 Degrees Vertical)	80H 71.5V
Maximum Candela At 90 Degrees Vertical	0 (0.0% Luminaire Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	1880.427 (8.2% Luminaire Lumens)
Cutoff Classification (deprecated)	N.A. (absolute)

LUMINAIRE CLASSIFICATION SYSTEM (LCS)

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	2193.8	N.A.	9.5
FM - Front-Medium (30-60)	6255.3	N.A.	27.2
FH - Front-High (60-80)	6026.1	N.A.	26.2
FVH - Front-Very High (80-90)	88.1	N.A.	0.4
BL - Back-Low (0-30)	1907.1	N.A.	8.3
BM - Back-Medium (30-60)	4738.0	N.A.	20.6
BH - Back-High (60-80)	1814.5	N.A.	7.9
BVH - Back-Very High (80-90)	4.2	N.A.	0.0
UL - Uplight-Low (90-100)	0.0	N.A.	0.0
UH - Uplight-High (100-180)	0.0	N.A.	0.0
Total	23027.1	N.A.	100.0
BUG Rating	B3-U0-G3		


COEFFICIENTS OF UTILIZATION



FLUX DISTRIBUTION

	Lumens	Percent Of Luminaire
Downward Street Side	14563.3	63.2
Downward House Side	8463.8	36.8
Downward Total	23027.1	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	23027.1	100.0

POLAR GRAPH




Maximum Candela = 13293.394 Located At Horizontal Angle = 80, Vertical Angle = 71.5

1 - Vertical Plane Through Horizontal Angles (80 - 260) (Through Max. Cd.)


2 - Horizontal Cone Through Vertical Angle (71.5) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



Distance In Units Of Mounting Height
Values Based On 20 Foot Mounting Height
1/2 Maximum Candela Trace Shown As Dashed Curve
(+) = Maximum Candela Point

LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:
Front: Low=2193.8, Medium=6255.3, High=6026.1, Very High=88.1
Back: Low=1907.1, Medium= 4738.0, High=1814.5, Very High=4.2
Uplight: Low=0.0, High=0.0

BUG Rating : B3-U0-G3