



IES ROAD REPORT

PHOTOMETRIC FILENAME : GCL2-80J-MV-27K-4-XX-250 S.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
 [TESTLAB] Scaled from NVLAP LM-79 for GCL2-80J-MV-30K-4-XX-275
 [ISSUEDATE] 6/20/2019
 [MANUFAC] Leotek Electronics USA LLC
 [LUMCAT] GCL2-80J-MV-27K-4-XX-260


CHARACTERISTICS

IES Classification	Type IV
Longitudinal Classification	Medium
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	25131
Downward Total Efficiency	N.A. (absolute)
Total Luminaire Efficiency	N.A. (absolute)
Luminaire Efficacy Rating (LER)	130
Total Luminaire Watts	193
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	14820.774
Maximum Candela Angle	80H 70V
Maximum Candela (<90 Degrees Vertical)	14820.774
Maximum Candela Angle (<90 Degrees Vertical)	80H 70V
Maximum Candela At 90 Degrees Vertical	0 (0.0% Luminaire Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	964.96 (3.8% Luminaire Lumens)
Cutoff Classification (deprecated)	N.A. (absolute)

LUMINAIRE CLASSIFICATION SYSTEM (LCS)

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	2487.7	N.A.	9.9
FM - Front-Medium (30-60)	6986.1	N.A.	27.8
FH - Front-High (60-80)	6436.9	N.A.	25.6
FVH - Front-Very High (80-90)	79.8	N.A.	0.3
BL - Back-Low (0-30)	2158.2	N.A.	8.6
BM - Back-Medium (30-60)	5236.9	N.A.	20.8
BH - Back-High (60-80)	1727.4	N.A.	6.9
BVH - Back-Very High (80-90)	17.5	N.A.	0.1
UL - Uplight-Low (90-100)	0.0	N.A.	0.0
UH - Uplight-High (100-180)	0.0	N.A.	0.0
Total	25130.5	N.A.	100.0
BUG Rating	B4-U0-G3		


COEFFICIENTS OF UTILIZATION



FLUX DISTRIBUTION


	Lumens	Percent Of Luminaire
Downward Street Side	15990.5	63.6
Downward House Side	9140.1	36.4
Downward Total	25130.6	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	25130.6	100.0

POLAR GRAPH




Maximum Candela = 14820.774 Located At Horizontal Angle = 80, Vertical Angle = 70
1 - Vertical Plane Through Horizontal Angles (80 - 260) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (70) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



Distance In Units Of Mounting Height
 Values Based On 20 Foot Mounting Height
 1/2 Maximum Candela Trace Shown As Dashed Curve
 (+) = Maximum Candela Point

LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:
Front: Low=2487.7, Medium=6986.1, High=6436.9, Very High=79.8
Back: Low=2158.2, Medium=5236.9, High=1727.4, Very High=17.5
Uplight: Low=0.0, High=0.0

BUG Rating : B4-U0-G3