



IES ROAD REPORT

PHOTOMETRIC FILENAME : GCL1-80J-MV-27K-2R-XX-230 S.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
 [TESTLAB] Scaled from NVLAP LM-79 for GCL1-80J-MV-30K-2R-XX-240
 [ISSUEDATE] 6/24/2019
 [MANUFAC] Leotek Electronics USA LLC
 [LUMCAT] GCL1-80J-MV-27K-2R-XX-230


CHARACTERISTICS

IES Classification	Type II
Longitudinal Classification	Medium
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	22848
Downward Total Efficiency	N.A. (absolute)
Total Luminaire Efficiency	N.A. (absolute)
Luminaire Efficacy Rating (LER)	133
Total Luminaire Watts	171.335
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	14332.902
Maximum Candela Angle	75H 72.5V
Maximum Candela (<90 Degrees Vertical)	14332.902
Maximum Candela At 90 Degrees Vertical)	75H 72.5V
Maximum Candela At 90 Degrees Vertical	0 (0.0% Luminaire Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	3705.478 (16.2% Luminaire Lumens)
Cutoff Classification (deprecated)	N.A. (absolute)

LUMINAIRE CLASSIFICATION SYSTEM (LCS)

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	2505.9	N.A.	11.0
FM - Front-Medium (30-60)	9090.6	N.A.	39.8
FH - Front-High (60-80)	5173.2	N.A.	22.6
FVH - Front-Very High (80-90)	154.6	N.A.	0.7
BL - Back-Low (0-30)	1648.8	N.A.	7.2
BM - Back-Medium (30-60)	2711.1	N.A.	11.9
BH - Back-High (60-80)	1504.7	N.A.	6.6
BVH - Back-Very High (80-90)	59.4	N.A.	0.3
UL - Uplight-Low (90-100)	0.0	N.A.	0.0
UH - Uplight-High (100-180)	0.0	N.A.	0.0
Total	22848.3	N.A.	100.0
BUG Rating	B3-U0-G3		


COEFFICIENTS OF UTILIZATION



FLUX DISTRIBUTION


	Lumens	Percent Of Luminaire
Downward Street Side	16924.3	74.1
Downward House Side	5924.0	25.9
Downward Total	22848.3	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	22848.3	100.0

POLAR GRAPH




Maximum Candela = 14332.902 Located At Horizontal Angle = 75, Vertical Angle = 72.5
1 - Vertical Plane Through Horizontal Angles (75 - 255) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (72.5) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



Distance In Units Of Mounting Height
 Values Based On 20 Foot Mounting Height
 1/2 Maximum Candela Trace Shown As Dashed Curve
 (+) = Maximum Candela Point

LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:
 Front: Low=2505.9, Medium=9090.6, High=5173.2, Very High=154.6
 Back: Low=1648.8, Medium=2711.1, High=1504.7, Very High=59.4
 Uplight: Low=0.0, High=0.0

BUG Rating : B3-U0-G3