



IES ROAD REPORT

PHOTOMETRIC FILENAME : GCL3-80J-MV-27K-2S-XX-270 S.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
 [TESTLAB] Scaled from NVLAP LM-79 for GCL3-80J-MV-30K-2S-XX-285
 [ISSUE DATE] 12/15/2022
 [MANUFAC] Leotek Electronics USA LLC
 [LUMCAT] GCL3-80J-MV-27K-2S-XX-270


CHARACTERISTICS

IES Classification	Type II
Longitudinal Classification	Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	26499
Downward Total Efficiency	N.A. (absolute)
Total Luminaire Efficiency	N.A. (absolute)
Luminaire Efficacy Rating (LER)	125
Total Luminaire Watts	211.3
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	15546.655
Maximum Candela Angle	305H 57.5V
Maximum Candela (<90 Degrees Vertical)	15546.655
Maximum Candela At 90 Degrees Vertical)	305H 57.5V
Maximum Candela At 90 Degrees Vertical	0 (0.0% Luminaire Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	2983.19 (11.3% Luminaire Lumens)
Cutoff Classification (deprecated)	N.A. (absolute)

LUMINAIRE CLASSIFICATION SYSTEM (LCS)

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	4216.0	N.A.	15.9
FM - Front-Medium (30-60)	12131.5	N.A.	45.8
FH - Front-High (60-80)	4911.3	N.A.	18.5
FVH - Front-Very High (80-90)	90.6	N.A.	0.3
BL - Back-Low (0-30)	2215.7	N.A.	8.4
BM - Back-Medium (30-60)	2013.2	N.A.	7.6
BH - Back-High (60-80)	901.2	N.A.	3.4
BVH - Back-Very High (80-90)	19.7	N.A.	0.1
UL - Uplight-Low (90-100)	0.0	N.A.	0.0
UH - Uplight-High (100-180)	0.0	N.A.	0.0
Total	26499.2	N.A.	100.0
BUG Rating	B3-U0-G2		


COEFFICIENTS OF UTILIZATION



FLUX DISTRIBUTION


	Lumens	Percent Of Luminaire
Downward Street Side	21349.4	80.6
Downward House Side	5149.9	19.4
Downward Total	26499.3	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	26499.3	100.0

POLAR GRAPH




Maximum Candela = 15546.655 Located At Horizontal Angle = 305, Vertical Angle = 57.5
1 - Vertical Plane Through Horizontal Angles (305 - 125) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (57.5) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



Distance In Units Of Mounting Height
 Values Based On 20 Foot Mounting Height
 1/2 Maximum Candela Trace Shown As Dashed Curve
 (+) = Maximum Candela Point

LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:
Front: Low= 4216.0, Medium=12131.5, High=4911.3, Very High=90.6
Back: Low=2215.7, Medium=2013.2, High=901.2, Very High=19.7
Uplight: Low=0.0, High=0.0

BUG Rating : B3-U0-G2