



IES ROAD REPORT

PHOTOMETRIC FILENAME : GCL2-80J-MV-27K-2S-XX-220 S.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
 [TESTLAB] Scaled from NVLAP LM-79 for GCL2-80J-MV-30K-2S-XX-225
 [ISSUEDATE] 6/24/2019
 [MANUFAC] Leotek Electronics USA LLC
 [LUMCAT] GCL2-80J-MV-27K-2S-XX-225


CHARACTERISTICS

IES Classification	Type II
Longitudinal Classification	Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	21923
Downward Total Efficiency	N.A. (absolute)
Total Luminaire Efficiency	N.A. (absolute)
Luminaire Efficacy Rating (LER)	136
Total Luminaire Watts	161
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	14604.317
Maximum Candela Angle	55H 58V
Maximum Candela (<90 Degrees Vertical)	14604.317
Maximum Candela At 90 Degrees Vertical)	55H 58V
Maximum Candela At 90 Degrees Vertical	0 (0.0% Luminaire Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	2394.99 (10.9% Luminaire Lumens)
Cutoff Classification (deprecated)	N.A. (absolute)

LUMINAIRE CLASSIFICATION SYSTEM (LCS)

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	3224.1	N.A.	14.7
FM - Front-Medium (30-60)	9475.6	N.A.	43.2
FH - Front-High (60-80)	4272.0	N.A.	19.5
FVH - Front-Very High (80-90)	101.7	N.A.	0.5
BL - Back-Low (0-30)	2003.1	N.A.	9.1
BM - Back-Medium (30-60)	1871.6	N.A.	8.5
BH - Back-High (60-80)	943.3	N.A.	4.3
BVH - Back-Very High (80-90)	31.7	N.A.	0.1
UL - Uplight-Low (90-100)	0.0	N.A.	0.0
UH - Uplight-High (100-180)	0.0	N.A.	0.0
Total	21923.1	N.A.	100.0
BUG Rating	B3-U0-G2		


COEFFICIENTS OF UTILIZATION



FLUX DISTRIBUTION


	Lumens	Percent Of Luminaire
Downward Street Side	17073.4	77.9
Downward House Side	4849.7	22.1
Downward Total	21923.1	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	21923.1	100.0

POLAR GRAPH




Maximum Candela = 14604.317 Located At Horizontal Angle = 55, Vertical Angle = 58
1 - Vertical Plane Through Horizontal Angles (55 - 235) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (58) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



Distance In Units Of Mounting Height
 Values Based On 20 Foot Mounting Height
 1/2 Maximum Candela Trace Shown As Dashed Curve
 (+) = Maximum Candela Point

LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:
Front: Low=3224.1, Medium=9475.6, High= 4272.0, Very High=101.7
Back: Low=2003.1, Medium=1871.6, High=943.3, Very High=31.7
Uplight: Low=0.0, High=0.0

BUG Rating : B3-U0-G2